

CAUTION STATEMENTS: When first using *Poly-Form™* on old die sets, care should be taken to watch for build up caused by deposits left by previously used oils. These deposits are very hard, but *Poly-Form™* will soften them. Once they are removed, this problem will cease to exist.

Poly-Form™ will remove laquer and some urethane paints. It will not affect enamel or epoxy paints. Most machine tools are painted with enamel paints.

Available in: 1-Gallon jugs, 5-Gallon Pails, 55-Gallon Drums

MIXING DIRECTIONS

	Water	Poly-Form™
PRECOATING	1	1
PUNCHING	10	1
BLANKING & FORMING	4	1
DRAWING WHILE FLOODING DIE	4	1

Premier Poly-Cut™, Poly-Cut™, Poly-Form™, contain no ingredients now known to be hazardous as defined by OSHA and the EPA.

Tullco, Inc.'s Product Guarantee

We guaranteed to work to your complete satisfaction or you do not have to pay for them! That's right, just ask your supplier for a 5-gallon pail of *Premier Poly-Cut™*, *Poly-Form™* to try on consignment. If, for any reason, you are not happy with the performance of our products, your local supplier will credit your account and you owe nothing! Our motto is: "If you like it, you buy it! If you don't like it, you do not have to pay for it!" You have my word on it!

DJ Tully
CEO, Tullco, Inc.

Premier Poly-Cut™

Poly-Cut™

Poly-Form™



**Polymer
Lubricants/Coolants**
for the Plastics and Metalworking
Industries

Tullco, Inc.
37A Osage Drive
Greenville, SC 29605
o: (864)299-8884
f: (864)299-8883